

# MS101III

## Powered Monitor Speaker



# MS101III

MS101III Rear Panel



A compact, convenient approach to high quality monitoring.

- 10 cm full-range speaker with 10 watts power amplifier
- 3 inputs: mic x 1 (phone), line x 2 (phone & RCA pin).
- Tone control (high/low)
- Line output for expanding your speaker system
- Options for convenient stand or wall mounting (sold separately)

### OPTIONS

BCS20-150/210  
Ceiling Bracket



BWS20-120/190  
Wall Bracket



BAS10  
Free-Angle Clamp



BMS-10A  
Mic Stand Adaptor



### GENERAL SPECIFICATIONS

Type	Bass-reflex powered speaker
Frequency response	75Hz to 18kHz
Sensitivity	97dB SPL (1m, 10W)
Power consumption	30W
Dimensions (W x H x D)	147 x 214 x 192mm (5.8" x 8.4" x 7.6")
Weight	2.5kg (5.5lbs)

### SPEAKER SECTION

Components	10cm cone x 1
Nominal impedance	4Ω

### AMPLIFIER SECTION

Output power	10W (@1kHz, THD=0.5%, RL=4Ω)
Input terminal	MIC input: Phone jack (-45dB, 2kΩ) LINE input1: RCA pin jack(-10dB, 10kΩ) LINE input2: Phone jack(-10dB, 10kΩ)
Output terminal	LINE OUT: Phonejack(-10dB, 600Ω)
Control	VOLUME, Tone control (Low/High)

### DIMENSIONS

unit : mm

